

Website: [www.armypublicschoolakhnoor.com](http://www.armypublicschoolakhnoor.com) Tele No 01924-254918 (Civil), 6807  
(Army)  
E-Mail: [apsakhnoor12@gmail.com](mailto:apsakhnoor12@gmail.com)



## ARMY PUBLIC SCHOOL AKHNOOR

(J & K)-181201

SCHOOL CODE-23515&

CBSE AFFILIATION NO - 780012

1862/APS/Quotation

01 Sep 2022

### CALL FOR QUOTATION: CONSTRUCTION OF HARD STANDING FOR ADDL VEHICLES PARKING AT APS AKHNOOR

1. Quotations are invited for construction of hard standing for addl vehicles parking at Army Public School, Akhnoor. The specifications for the construction of hard standing for addl vehicles parking are attached as **Appx A**.
2. The following specifications are also required to be mentioned in the quotation:-
  - (a) Total Cost.
  - (b) Discount.
  - (c) GST, freight and any other charges.
  - (d) Warranty / Guarantee
  - (e) Maintenance with replacement and Repair
3. Earnest Money in form of Demand Draft for @5% of total cost will be required to be deposited by the selected bidder as security of bid.
4. You are requested to send your quotations by 15 Sep 2022 positively dully addressed in a sealed envelope. Quotation will be dropped in to the Box kept in the APS Akhnoor upto 15 Sep (1500 hours). In case of quotations send by post, no quotation beyond the stipulated time frame shall accepted. Bids not in conformity with the quoted specification will be rejected.



  
(Geeta Devi)  
Principal

Development of Parking Area near Main Gate at APS-Akhnoor.

S.No.	Description	Unit	Qty.	Remarks
	<b>Size of Parking 50x25 mtr. (1250 Sqm) or 13,600 sqft. (approx)</b>			
1	Preparation and consolidation of sub grade with power road roller of 8 to 12 tonne capacity after excavating earth to an average of 22.5 cm depth, dressing to camber and consolidating with road roller including making good the undulations etc. and re-rolling the sub grade and disposal of surplus earth with lead upto 50 metres.	sqm	1250.00	
2	Supply & Laying, spreading and compacting 53 mm to 22.4 mm size stone aggregates of specified sizes to WBM specifications in uniform thickness, hand picking, rolling with 3 wheeled road/vibratory roller 8-10 tonne capacity in stages to proper grade and camber, applying and brooming requisite type of screening / binding material to fill up interstices of coarse aggregate, watering and compacting to the required density . (Thickness approx 22.5 Cm)	sqm	1250.00	
3	Supplying & laying in position cement concrete of specified grade 1:3:6 (1 cement : 3 fine sand : 6 graded stone aggregate 20 mm nominal size) smooth finish and maintaining the slope. (Thickness approx 75 mm)	Sqm	1250.00	
4	Providing and laying 60mm thick factory made cement concrete interlocking paver block of M 30 grade made by block making machine with strong vibratory compaction, of approved size, design & Shape, laid in required colour and pattern over and including 50mm thick compacted bed of coarse sand, filling the joints with line sand etc. all complete	Sqm	1250.00	
5	Providing and laying edging 60 x 60 mm thick with cement concrete 1:2:4 (1 cement : 2 coarse sand : 4 graded stone aggregate 20mm nominal size).	Rmt	160.00	



(GEEJA DEVI)

Principal

Army Public School  
Akhnoor