




ARMY PUBLIC SCHOOL AKHNOOR
(J & K)-181201
SCHOOL CODE-23515&
CBSE AFFILIATION NO - 730017

1862/APS/Quotation

20 Oct 2022

**CALL FOR QUOTATION: RENOVATION OF EXISTING
BASKETBALL COURT AT APS AKHNOOR**

1. Quotations are invited for renovation of existing basketball court at Army Public School, Akhnoor. The specifications for the renovation of existing basketball court are attached as **Appx A**.
2. The following specifications are also required to be mentioned in the quotation:-
 - (a) Total Cost.
 - (b) Discount.
 - (c) GST, freight and any other charges.
 - (d) Warranty / Guarantee
 - (e) Maintenance with replacement and Repair
3. Earnest Money in form of Demand Draft for @5% of total cost will be required to be deposited by the selected bidder as security of bid.
4. You are requested to send your quotations by 05 Nov 2022 positively dully addressed in a sealed envelope. Quotation will be dropped in to the Box kept in the APS Akhnoor upto 05 Nov (1500 hours). In case of quotations send by post, no quotation beyond the stipulated time frame shall accepted. Bids not in conformity with the quoted specification will be rejected.


(Geeta Devi)
Principal

Technical DetailsRENOVATION OF EXISTING BASKET BALL COURT AT APS- AKHNOOR

S/No.	Brief Specification	Remark
1.	<p><u>Scope of Work:-</u> Renovation of existing basket ball court (Size 28.5 mtr. x 18 mtr.) or 5520 Sq.ft. (approximate) with cement concrete surface basketball Court ITF Approved System</p>	
2.	<p><u>Salient features of work:</u></p> <ul style="list-style-type: none"> ➤ Dismantling of top layer of cement concrete platform manually/ by mechanical at least minimum 25-40 mm etc. including disposal of unserviceable materials near dumping ground. ➤ Laying of cement concrete flooring with concrete hardener topping, under layer 40 mm thick cement concrete on existing surface with cement concrete 1:1½:3 (1 Cement: 1½ coarse sand (zone-III): 3 graded stone aggregate 10 mm nominal size) and top layer 6 mm thick cement hardener consisting of mix 1:2 (1 cement hardener mix: 2 graded core sand) by volume, hardening compound mixed @ 2 litre per 50 kg of cement or as per specifications with smooth finishing on top surface. ➤ Providing and fixing glass strips in joints of terrazo/ cement concrete floors. 40 mm wide and 3 mm thick ➤ Making Line of Basket ball Court with Synthetic enamel paint or epoxy paint as per International Standards 	